

interatletika™

PRODUCTION AND SALE OF CHILDREN'S AND OUTDOOR
EQUIPMENT

Customer support:


☎ +38 095 273 81 53

play.interatletika.com

✉ export.team@interatletika.com

LK903 - Trampoline
LK903-R - Trampoline
LK903-PU - Trampoline
LK903-R-PU - Trampoline
LK903-H-R - Trampoline "Take-off area"
LK903-H-R-PU - Trampoline "Take-off area"
LK904-S - Trampoline "Pentagon"
LK904-S-PU - Trampoline "Pentagon"
LK904-L - Trampoline "Pentagon"
LK904-L-PU - Trampoline "Pentagon"
LK905 - Trampoline "Petal"
LK905-PU - Trampoline "Petal"

DATA SHEET



CONTENT

1. GENERAL INFORMATION	3
2. TECHNICAL DATA	3
3. COMPLETE SET	3
4. CERTIFICATE OF ACCEPTANCE, PACKAGING AND CONSERVATIONОшибка! Закладка не определена.	
5. INFORMATION ON STORAGE, TRANSPORT AND DISPOSALОшибка! Закладка не определена.	
6. INSPECTION AND TESTING	Ошибка! Закладка не определена.
7. TECHNICAL MAINTENANCE	4
8. INSTRUCTION FOR SAFE USE	Ошибка! Закладка не определена.
9. INSTALLATION INSTRUCTIONS	5

FOR NOTES

[illegible]

1. ОСНОВНІ ВІДОМОСТІ

1.1 Article number _____.

1.2 Name _____.

1.3 Manufacturer LLC«Company Sporttehnika», Ukraine, city of Chernihiv, Ivana Mazepy str., 78.

1.4 Serial number and production date: _____, «____» _____ 20__ year.

1.5 Produced in accordance with regulatory documents: TC AT 28.9-31597759-001:2012.

1.6 The product is designed for children and creates conditions for:

- physical development of the child;

- development of movements coordination, overcoming fear of heights, development of agility and courage, sense of teamwork in team games.

The manufacturer can make changes to the product design to improve its performance, change the design, etc.

This document may not contain a description of such changes, but applies to the following modified products.

2. TECHNICAL DATA

№	Article number	Length, mm	Width, mm	Trampoline fabric, mm	Weight, kg
1	LK903	2009	2009	1510x1510	142
2	LK903-PU	2009	2009	1510x1510	174
3	LK903-R	1390	1390	Ø830	96
4	LK903-R-PU	1390	1390	Ø830	121
5	LK903-H-R	1390	1390	Ø830	96
6	LK903-H-R-PU	1390	1390	Ø830	121
7	LK904-S	1390	1390	790x760	99
8	LK904-S-PU	1390	1390	790x760	126
9	LK904-L	2009	2009	1380x1320	172
10	LK904-L-PU	2009	2009	1380x1320	221
11	LK905	2009	2009	1310x1310	171
12	LK905-PU	2009	2009	1310x1310	218

Age range, years	>5
Weight limits, kg	до 120
Number of users simultaneously	1
Maximum jump height, m	0,6

3. COMPLETE SET

The product's components are listed in the 'Component List' and 'Fastening Kit' supplied with the product.

4. CERTIFICATE OF ACCEPTANCE, PACKAGING AND CONSERVATION

Product _____, serial number _____ complies with regulatory documents TC AT 28.9-31597759-001:2012 and recognised as serviceable.

OTC mark: «____» _____ 20__ year.

Date

Full name

P.S.

Packed by LLC «Company Sporttehnika» in accordance with the requirements of regulatory documents.

«____» _____ 20__ year.

Date of packing

Packed by _____

Full name

Signature

Information on conservation and deconservation during operation

Conservation date	Conservation method	Conservation period	Deconservation date	Name of the company (organisation)	Position, full name	Signature

5. INFORMATION ON STORAGE, TRANSPORT AND DISPOSAL

The product is transported in the manufacturer's packaging by any means of transport that ensures its safety and protection from external factors (rain, snow, sunlight, water, high humidity, etc.).

Information about transportation

Date		Brand, state number of the ca/trailer	Position, full name	Signature
Departure	Arrival			

Before installation, store the product in the original packaging in dry, closed rooms with natural air ventilation.

If it is necessary to transport the product to another location after use, it is recommended to use the manufacturer's packaging.

If long-term storage of the product is required, the following storage rules must be observed (the list of conditions is not complete):

- place the product in a closed dry room with natural ventilation;
- protect the product from external factors (dust, water drops, etc.) with a large plastic bag, leaving space for free air circulation;

- take other measures to preserve the appearance and characteristics of the product during storage.

When removing the product from storage and preparing for installation, follow the next recommendations:

- remove the product from the packaging material (polyethylene, cardboard, other packaging materials);
- remove dust and other contaminants from the surface of the product;
- check completeness and absence of parts damage.

Storage information

Date		Product storage conditions	Full name	Signature
Putting into storage	Removal from storage			

After the end of the equipment's service life, the buyer independently determines the procedure for its use. If you decide to recycle, contact the seller or specialized organizations.

The equipment does not contain harmful impurities and materials that can harm your health and is not subject to special recycling.

6. INSPECTION AND TESTING

Before starting the operation of the product, it is visually inspected, checked: the integrity of paint coating, fasteners and structural strength.

If there are concrete support parts of the product, make sure that they are securely fixed and do not move.

Check that the equipment and site are free from packaging materials, construction debris and other foreign objects.

Check the proper condition of the shock-absorbing surfaces on the playground.

7. TECHNICAL MAINTENANCE

Timely maintenance of the product is the responsibility of the buyer (or a responsible person) and includes:

1. Daily inspection - before using the product, check its performance, visual inspection for the absence of breakdowns, damage, sharp edges on components and parts, structural integrity, strength of wooden structures and element connection points, absence of unnecessary objects on the platforms. If the product is damaged, fully or partially inoperable, or otherwise defective, it is prohibited to use the product.

2. Scheduled inspection is carried out every three months.

It involves a detailed visual and operational inspection of the operation and stability of the equipment, especially with regard to any wear.

In the process of inspection, they determine:

- cleanliness and appearance of the surface of the playground and equipment;
- maintaining distances from parts of the equipment to the surface of the playground;
- absence of protruding parts of the foundations;
- absence of defects/malfunctions of equipment elements;
- wear of moving parts;
- structural integrity of equipment.

Special attention should be paid to hidden and inaccessible parts of the equipment.

3. Annual inspection is held every 12 months to establish the overall safety level of the equipment.

In the process of visual and functional inspection it is determined:

- structural stability;
- integrity of the foundation;
- strength of units of item elements connection;
- wear of sliding surfaces and grips.

Special attention should be given to:

- assessing the impact of weather events;
- the presence of rot or corrosion;
- parts that are closed to access during the entire period of operation. All parts of the trampoline must be checked, including: the fabric, springs, shock-absorbing surface and steel construction.

If the springs show any signs of excessive corrosion, deformation, excessive wear at the suspension point

exceeding 15% of the spring wire thickness, cracks or other damage, the spring must be replaced immediately.

If the trampoline bounce is weak, the springs need to be replaced. In a removed spring, the coils should touch each other. If not, it means that the spring is overstretched due to overload and needs to be replaced. Use a spring hook to remove or install the springs.

After 1 year of operation, all equipment components should be checked for signs of brittleness and replaced if necessary. After prolonged exposure to ultraviolet radiation, some colour fading and brittleness of the trampoline fabric elements can be expected. In case of breakage of the fabric slats, steel cable or cable clamp, the fabric should be replaced immediately.

In case of contamination, wash with water without using aggressive detergents.

If cracks or delamination of the shock-absorbing coating from the construction appear, it should be replaced.

NOTE 1. The area under the trampoline should be cleaned at least once a year, and its surface should be water-permeable. Puddles are unacceptable.

NOTE 2. The main annual inspection may require digging up or dismantling (unscrewing) individual equipment or parts thereof. The annual inspection must be carried out by the manufacturer or an authorised service centre.

The results of the inspection, repair or replacement of equipment components must be recorded in the maintenance log.

Maintenance recording

Date and type of inspection	Name of the work done	Remarks on the technical condition	Position, full name, signature of the responsible person

8. INSTRUCTION FOR SAFE USE

Before operating the product, conduct a visual inspection, check the fasteners and structural strength.

The equipment is used on the playgrounds without constant supervision by operating personnel. In order to ensure the safe operation of the product, the owner must conduct a daily visual inspection. If malfunctions are detected during the inspection, they must be immediately eliminated, and if this is not possible, the equipment must be closed for users.

Examples of impact-absorbing coatings

Examples of impact absorbing coatings			
Material ¹	Description	Minimal depth, mm	Height of fall, mm
Turf			≤1000
Tree bark	grain size 20-80 mm	200	≤2000
		300	≤3000
Sawdust	grain size 5-30 mm	200	≤2000
		300	≤3000
Sand ²	grain size 0,2-2 mm	200	≤2000
		300	≤3000
Gravel ²	grain size 2-8 mm	200	≤2000
		300	≤3000
Other materials ³	Characteristics of the tested material		Critical height of fall obtained during testing
<div>1. Materials specially prepared for playgrounds.</div> <div>2. There should not be any clay inclusions.</div> <div>3. The grain size is obtained by sieving through a sieve as in EN933-1.</div>			

WARNING! Operating the product without an impact-absorbing coating may result to serious injury during falling down.

Playground surface materials with low impact-absorbing features should only be used outside the fall zone.

Product use:

- it is recommended to show or tell children how to use the equipment;
- during use it is recommended to hold onto handrails, railings, handles;
- it is forbidden to use until the completion of its full and final installation;
- it is forbidden to use by users of a different age and weight category;
- before using clear the surface from foreign objects, sharp elements, protrusions;
- it is forbidden to move the product elements which are not intended for this;
- do not use in difficult weather conditions (ice, snow, rain, hail, strong wind, etc.), in which there is a possibility of injury to the child.

The manufacturer is not responsible for the consequences:

- poor quality and improper installation of the product;
- use of low-quality materials and inadequate qualifications of personnel during installation of the product;
- use of the product earlier than the period necessary to fix the product in the soil or other material;
- design changes to the product that caused injury;
- lack of proper adult control;
- violation of age and weight restrictions by users;
- damage to the product due to improper storage, installation or use of the product for purposes other than those intended.

9. INSTALLATION INSTRUCTIONS

Installation of the product can be carried out by the manufacturer, service centre or other legal entities and individuals who have the necessary material and technical base and qualifications.

The product is installed on a prepared flat area, free from debris, trees and other obstacles that interfere with installation (when installed in winter, the area shall be additionally free from snow). The required size of the site is determined by the fall zone of the equipment. When installing in winter on natural ground, it is recommended to choose a site with compacted soil in the area of foundation placement.

The height difference of the prepared site should be:

- a) no more than 50 mm for natural substrates, including substrates with subsequent shock-absorbing coating.
- b) no more than 10 mm for hard substrates (asphalt, concrete), including substrates with subsequent

application of a synthetic protective coating.









Before starting the installation, you must:

- study the documentation supplied with the product;
- check the completeness in accordance with the documents supplied with the product;
- remove the original packaging from the component part;
- comply with safety requirements.

WARNING! The presence and participation of children during the installation of the product is not allowed.

Install the product in stages, following the instructions in the appendix.

Table №1 – General view

LK903	LK903-PU
	
LK903-R	LK903-R-PU
	
LK903-H-R	LK903-H-R-PU
	
LK904-S	LK904-S-PU
	







Table №2 – Safety zone





Picture 1 – Installation scheme