

interatletika™

PRODUCTION AND SALE OF PLAYGROUND AND OUTDOOR
EQUIPMENT

Customer support:


☎ +38 095 273 81 53

play.interatletika.com

✉ export.team@interatletika.com

LK624-M – Playground complex Smile M

DATA SHEET



CONTENT

1. GENERAL INFORMATION	3
2. TECHNICAL DATA	3
3. COMPLETE SET	3
4. CERTIFICATE OF ACCEPTANCE, PACKAGING AND CONSERVATION	3
5. INFORMATION ON STORAGE, TRANSPORT AND DISPOSAL	3
6. INSPECTION AND TESTING	4
7. PRODUCT MAINTENANCE	4
8. INSTRUCTIONS FOR SAFE USE	5
9. INSTALLATION INSTRUCTIONS	5

FOR NOTES

This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.

1. GENERAL INFORMATION

1.1 Article number _____.

1.2 Name _____.

1.3 Manufacturer LLC«Company Sporttechnika», Ukraine, city of Chernihiv, Ivana Mazepy St., 78.

1.4 Serial number and production date: _____, «____» _____ 20__ year.

1.5 Produced in accordance with regulatory documents: TC AT 28.9-31597759-001:2012.

1.6 The product is designed for children and creates conditions for:

- physical development of the child;

- development of coordination of movements, overcoming fear of heights, development of agility and courage, a sense of teamwork in team games.

The manufacturer can make changes to the product design to improve its performance, change the design, etc.

This document may not contain a description of such changes, but applies to the following modified products.

2. TECHNICAL DATA

	LK624-M
Length, mm	9393
Width, mm	3674
Height, mm	2045
Height of fall, mm	1550
Weight, kg	735.9
Age range, years	from 3
Weight limits, kg	Up to 100

3. COMPLETE SET

Complete set of the product is given in the «Complete set information» and «Complete set of fasteners», supplied with the product.

4. CERTIFICATE OF ACCEPTANCE, PACKAGING AND CONSERVATION

Product _____, serial number _____ complies with regulatory documents TC AT 28.9-31597759-001:2012 and recognised as serviceable.

OTC mark: «____» _____ 20__ year.

Date

Full name

P.S.

Packed by LLC «Company Sporttechnika» in accordance with the requirements of regulatory documents.

«____» _____ 20__ year.

Date of packing

Packed by _____

Full name

Signature

Information on conservation and deconservation during operation

Conservation date	Conservation method	Conservation period	Deconservation date	Name of the company (organisation)	Position, full name	Signature

5. INFORMATION ON STORAGE, TRANSPORT AND DISPOSAL

The product is transported in the manufacturer's packaging by any means of transport that ensures its safety and protection from external factors (rain, snow, sunlight, water, high humidity, etc.).

Information about transportation

Date		Brand, state number of the ca/trailer	Position, full name	Signature
Departure	Arrival			

Before installation, store the product in the original packaging in dry, closed rooms with natural air ventilation.

If it is necessary to transport the product to another location after use, it is recommended to use the manufacturer's packaging.

If long-term storage of the product is required, the following storage rules must be observed (the list of conditions is not complete):

- place the product in a closed dry room with natural ventilation;

- protect the product from external factors (dust, water drops, etc.) with a large plastic bag, leaving space for free air circulation;

- take other measures to preserve the appearance and characteristics of the product during storage.

When removing the product from storage and preparing for installation, follow the next recommendations:

- remove the product from the packaging material (polyethylene, cardboard, other packaging materials);

- remove dust and other contaminants from the surface of the product;

- check completeness and absence of parts damage.

Storage information

Date		Product storage conditions	Full name	Signature
Putting into storage	Removal from storage			

After the end of the equipment's service life, the buyer independently determines the procedure for its use. If you decide to recycle, contact the seller or specialized organizations.

The equipment does not contain harmful impurities and materials that can harm your health and is not subject to special recycling.

6. INSPECTION AND TESTING

Before starting the operation of the product, it is visually inspected, checked: the integrity of paint coating, fasteners and structural strength.

If there are concrete support parts of the product, make sure that they are securely fixed and do not move.

Check that the equipment and site are free from packaging materials, construction debris and other foreign objects.

Check the proper condition of the shock-absorbing surfaces on the playground.

7. PRODUCT MAINTENANCE

Timely maintenance of the product is the responsibility of the buyer (or a responsible person) and includes:

1. Daily inspection - before using the product, check its performance, visual inspection for the absence of breakdowns, damage, sharp edges on components and parts, structural integrity, strength of wooden structures and element connection points, absence of unnecessary objects on the platforms. If the product is damaged, fully or partially inoperable, or otherwise defective, it is prohibited to use the product.

2. Scheduled inspection is carried out every three months.

It involves a detailed visual and operational inspection of the operation and stability of the equipment, especially with regard to any wear.

In the process of inspection, they determine:

- cleanliness and appearance of the surface of the playground and equipment;
- maintaining distances from parts of the equipment to the surface of the playground;
- absence of protruding parts of the foundations;
- absence of defects/malfunctions of equipment elements;
- wear of moving parts;
- structural integrity of equipment.

Special attention should be paid to hidden and inaccessible parts of the equipment.

3. Annual inspection is held every 12 months to establish the overall safety level of the equipment.

In the process of visual and functional inspection it is determined:

- structural stability;
- integrity of the foundation;
- strength of units of item elements connection;
- wear of sliding surfaces and grips.

Special attention should be given to:

- assessing the impact of weather events;
- the presence of rot or corrosion;
- parts that are closed to access during the entire period of operation.

The results of the inspection, repair or replacement of equipment components must be recorded in the maintenance record sheet.

Maintenance recording

Date and type of inspection	Name of the work done	Remarks on the technical condition	Position, full name, signature of the responsible person

8. INSTRUCTIONS FOR SAFE USE

WARNING! Children are allowed on the equipment only under adult control.

Before operating the product, conduct a visual inspection, check the fasteners and structural strength.

The equipment is used on the playgrounds without constant supervision by operating personnel. In order to ensure the safe operation of the product, the owner must conduct a daily visual inspection. If malfunctions are detected during the inspection, they must be immediately eliminated, and if this is not possible, the equipment must be closed for users.

There should not be any foreign objects, sharp elements, protrusions on the surface of the playground.

Under playground equipment with a free-fall height of more than 600 mm, an impact-absorbing coating must be provided over the entire fall zone. With a free fall height of less than 1000 mm, a turf shock-absorbing coating is allowed.

Examples of impact-absorbing coatings

Material¹	Description	Minimal depth, mm	Height of fall, mm
Turf			≤1000
Tree bark	grain size 20-80 mm	200	≤2000
		300	≤3000
Sawdust	grain size 5-30 mm	200	≤2000
		300	≤3000
Sand ²	grain size 0,2-2 mm	200	≤2000
		300	≤3000
Gravel ²	grain size 2-8 mm	200	≤2000
		300	≤3000
Other materials ³	Characteristics of the tested material		Critical height of fall obtained during testing
1. Materials specially prepared for playgrounds. 2. There should not be any clay inclusions. 3. The grain size is obtained by sieving through a sieve as in EN933-1.			

WARNING! Operating the product without an impact-absorbing coating may result to serious injury during falling down.

Playground surface materials with low impact-absorbing features should only be used outside the fall zone.

Product use:

- it is recommended to show or tell children how to use the equipment;
- during use it is recommended to hold onto handrails, railings, handles;
- it is forbidden to use until the completion of its full and final installation;
- it is forbidden to use by users of a different age and weight category;
- before using clear the surface from foreign objects, sharp elements, protrusions;
- it is forbidden to move the product elements which are not intended for this;
- do not use in difficult weather conditions (ice, snow, rain, hail, strong wind, etc.), in which there is a possibility of injury to the child.

The manufacturer is not responsible for the consequences:

- poor quality and improper installation of the product;
- use of low-quality materials and inadequate qualifications of personnel during installation of the product;
- use of the product earlier than the period necessary to fix the product in the soil or other material;
- design changes to the product that caused injury;
- lack of proper adult control;
- violation of age and weight restrictions by users;
- damage to the product due to improper storage, installation or use of the product for purposes other than those intended.

9. INSTALLATION INSTRUCTIONS

Installation of the product can be carried out by the manufacturer, service centre or other legal entities and individuals who have the necessary material and technical base and qualifications.

The product is installed on a prepared flat area, free from debris, trees and other obstacles that interfere with installation (when installed in winter, the area shall be additionally free from snow). The required size of the site is determined by the fall zone of the equipment. When installing in winter on natural ground, it is recommended to choose a site with compacted soil in the area of foundation placement.

The height difference of the prepared site should be:

- a) no more than 50 mm for natural substrates, including substrates with subsequent shock-absorbing coating.
- b) no more than 10 mm for hard substrates (asphalt, concrete), including substrates with subsequent application of a synthetic protective coating.

Before starting the installation, you must:

- study the documentation supplied with the product;
- check the completeness in accordance with the documents supplied with the product;
- remove the original packaging from the component part;
- comply with safety requirements.

To avoid cracking of the wood, for screws with a diameter of more than 4 mm, drill holes with a diameter of 0.6...0.7 mm to a depth of 0.8 of the screw's length.

WARNING! The presence and participation of children during the installation of the product is not allowed.

Install the product in stages, following the instructions in the appendix.

Technical drawing of a building plan, showing a central rectangular area with a grid pattern, surrounded by a larger, irregularly shaped area. The drawing includes various dimensions and labels:

- Overall width: 12793
- Overall height: 7167
- Central rectangular area dimensions: 1500 (width) x 1500 (height).
- Dimensions for the central area's internal structure: 1000 (width) x 2000 (height).
- Dimensions for the surrounding area: 1000 (width) x 2000 (height).
- Dimensions for the surrounding area's internal structure: 1000 (width) x 2000 (height).
- Dimensions for the surrounding area's internal structure: 1000 (width) x 2000 (height).
- Dimensions for the surrounding area's internal structure: 1000 (width) x 2000 (height).

Technical drawing showing the layout of a lighting fixture installation. The drawing includes dimensions for the overall layout and individual fixture sizes.

Overall Dimensions:


- Overall width: 1072
- Overall height: 1000

Fixture Dimensions and Layout:


- Top left fixture: 900 (width) x 450 (height)
- Top right fixture: 900 (width) x 450 (height)
- Bottom left fixture: 800 (width) x 450 (height)
- Bottom right fixture: 800 (width) x 450 (height)
- Central fixture: 1475 (width) x 600 (height)
- Bottom center fixture: 1900 (width) x 850 (height)
- Bottom right cluster: 1100 (width) x 1100 (height)

Spacing Dimensions:


- Horizontal spacing: 962, 1338, 600, 1100, 800, 1100, 1800, 1100
- Vertical spacing: 1038, 762, 604, 1038, 762, 574, 574



Picture 1 – Assembly scheme of frame




Picture 2 – General view of tunnel




Picture 3 – Assembly scheme of section (Holes in ascents with 4/5 mortises, pos. 26, 27, drill at assembly site)

Table №3 – Completeness of central section

<i>Pos.</i>	<i>Name</i>	<i>Weight, kg</i>	<i>Q-ty</i>
1	<i>Rack 1</i>	40	1
2	<i>Rack 1.1</i>	42	1
3	<i>Rack 1.2</i>	41	1
4	<i>Rack 1.3</i>	24	1
5	<i>Rope mesh with fastening</i>	5	1
6	<i>Clamping plate D89 mm</i>		4
7	<i>Clamping plate D60 mm</i>		8
8	<i>Washer 12-A2 DIN125 (flat)</i>		24
9	<i>Washer 8-A2 DIN125 (flat)</i>		33
10	<i>Stud M12*25.A2-70 ISO7380 (half-round)</i>		24
11	<i>Crosspiece D60-L570 (4 ears)</i>	3	1
12	<i>Crosspiece D60-L570 (3 ears)</i>	23	1
13	<i>Tunnel</i>	9	1
14	<i>Upper cover plate of tube</i>	3	2
15	<i>Lower cover plate of tube</i>	5	2
16	<i>Upper tunnel rim</i>		2
17	<i>Lower tunnel rim</i>		2
18	<i>Stud M8x30.A2-70 ISO7380-2 (press washer) stainless</i>		20
19	<i>Stud M8x35.A2 ISO7380-2 (press washer) stainless</i>		33
20	<i>Screw 4*25-A2, DIN7997 (countersunk-univ., PZ) stainless</i>		20
21	<i>Rope 1.76 m</i>		1
22	<i>Rope 1.73 m</i>		1
23	<i>Rope 1.44 m</i>		1
24	<i>Rope 1.67 m</i>		1
25	<i>Embedded element D89x500mm (with fastening)</i>	7	7
26	<i>Ascent with 5 mortises</i>	15	2
27	<i>Ascent with 4 mortises</i>	13	1
28	<i>Nut M8.A2-70 DIN1587 (cap nut) stainless</i>		33
29	<i>Ring D89</i>		2
30	<i>Ring D60</i>		4




Picture 4 – Assembly scheme of slide 0,7m



Picture 4.1 – Assembly scheme of slide 0,7m

Table №3 – Completeness of slide 0,7m


<i>Pos.</i>	<i>Name</i>	<i>Weight, kg</i>	<i>Q-ty</i>
1	<i>Slide embedded element (angle bar)</i>	5	1
2	<i>Slide 0.7m</i>	24	1
3	<i>Ascent frame</i>	9	1
4	<i>Cover plate Smile</i>		2
5	<i>Slide site</i>		1
6	<i>Ascent sidewall right</i>	12	1
7	<i>Ascent sidewall left</i>	12	1
8	<i>Bent shield</i>	7	1
9	<i>Table angle bar</i>		4
10	<i>Nut M6.A2-70 DIN1587 (cap nut) stainless</i>		14
11	<i>Nut M8.A2-70 DIN1587 (cap nut) stainless</i>		16
12	<i>Nut M6x10.A2-70 ERICSON (flat) stainless</i>		4
13	<i>Stud M6*16.A2-70, ISO7380 (half-round) stainless</i>		2
14	<i>Stud M6*25.A2-70, ISO7380 (half-round) stainless</i>		6
15	<i>Stud M6*40.A2-70, ISO7380 (half-round) stainless</i>		2
16	<i>Stud M8*50.A2-70, ISO7380 (half-round) stainless</i>		8
17	<i>Stud M8*60.A2-70, ISO7380 (half-round) stainless</i>		8
18	<i>Stud M6*25.A2-70, DIN7991 (countersunk) stainless</i>		8
19	<i>Stud M8*30.A2-70, DIN7991 (countersunk) stainless</i>		4
20	<i>Nut M8 A2-70, DIN985 (lock nut) stainless</i>		4
21	<i>Washer 6-A2 DIN125 (flat)</i>		4
22	<i>Washer 6-A2 DIN9021 (enlarged) stainless</i>		12
23	<i>Washer 8-A2 DIN125 (flat)</i>		16
24	<i>Screw 4*25-A2, DIN7997 (countersunk-univ., PZ) stainless</i>		6
25	<i>Anchor assembly</i>		4



Pos.	Name	Weight, kg	Q-ty
1	Rack 2m	40	1
2	Crossbar for suspended platforms	15	1
3	Clamping plate D89 mm		4
4	Washer 12-A2 DIN125 (flat)		8
5	Washer 8-A2 DIN125 (flat)		9
6	Stud M12*25.A2-70 ISO7380 (half-round)		8
7	Suspended platforms	16	1
8	Slide 0.7m	77	1
9	Embedded element D89x500mm (with fastening)	7	1
10	Slide panel	14	1
11	Smiling smile		2
12	Winking smile		2
13	Ring D89		2
14	Nut M8.A2-70 DIN1587 (cap nut) stainless		9
15	Stud M8x35-A2 ISO7380-2 (press washer) stainless		9
16	Screw 4*25-A2, DIN7997 (countersunk-univ., PZ) stainless		16


Picture 5 – Section assembly scheme

«Assembly scheme of section with slide 1,2m»




Pos.	Name	Weight, kg	Q-ty
1	Rack 1.5m	33	1
2	Welded crossbar	38	1
3	Slide 1.2m (Smile)	105	1
4	Clamping plate D89 mm		4
5	Washer 12-A2 DIN125 (flat)		8
6	Washer 8-A2 DIN125 (flat)		16
7	Stud M12*25.A2-70 ISO7380 (half-round)		8
8	Embedded element D89x500mm (with fastening)	7	2
9	Panel for slide	14	1
10	Smile in glasses		2
11	Smile with stars		2
12	Triangular panel	11	1
13	Board for drawing	3	1
14	Ring D530 mm		2
15	Panel Labyrinth	3	1
16	Screw 4*25-A2, DIN7997 (countersunk-univ., PZ) stainless		16
17	Nut M8.A2-70 DIN1587 (cap nut) stainless		16
18	Stud M8x35-A2 ISO7380-2 (press washer) stainless		16
19	Stud M8x70.A2-70 ISO7380-2 (press washer) stainless		6
20	Nut M8x12.A2-70 ERICSON (flat) stainless		6
21	Ring D89		2

Picture 6 – Section assembly scheme




<i>Pos.</i>	<i>Name</i>	<i>Weight, kg</i>	<i>Q-ty</i>
1	Slide embedded element	5	1
2	Slide 1.2m (Smile)	37	1
3	Ascent frame 1.2m	11	1
4	Cover plate Smile		2
5	Slide site		1
6	Slide sidewall right		1
7	Slide sidewall left		1
8	Ascent shield	11	1
9	Table angle bar		4
10	Nut M6.A2-70 DIN1587 (cap nut) stainless		14
11	Nut M8.A2-70 DIN1587 (cap nut) stainless		24
12	Nut M6x10.A2-70 ERICSON (flat) stainless		4
13	Stud M6*16.A2-70, ISO7380 (half-round) stainless		2
14	Stud M6*25.A2-70, ISO7380 (half-round) stainless		6
15	Stud M6*40.A2-70, ISO7380 (half-round) stainless		2
16	Stud M8*50.A2-70, ISO7380 (half-round) stainless		12
17	Stud M8*60.A2-70, ISO7380 (half-round) stainless		12
18	Stud M6*25.A2-70 DIN7991 (countersunk) stainless		8
19	Stud M8*30.A2-70 DIN7991 (countersunk) stainless		4
20	Nut M8 A2-70, DIN985 (lock nut) stainless		4
21	Washer 6-A2 DIN125 (flat)		4
22	Washer 6-A2 DIN9021 (enlarged) stainless		12
23	Washer 8-A2 DIN125 (flat)		24
24	Screw 4*25-A2, DIN7997 (countersunk-univ., PZ) stainless		6
25	Anchor assembly		4

Picture 7 – Completeness of slide 1,2m (Assembly scheme of slide is similar to slide 0,7m)




Picture 8 – Concreting

Appendix



Picture 9



Picture 10