
interatletika[™]

PRODUCTION AND SALE OF SPORTS GOODS

Customer support:
+38 095 273 81 53
play.interatletika.com

DATA SHEET

Game complex «Funny islands» LK110



CONTENT

1. GENERAL INFORMATION	3
2. PRODUCT ASSEMBLY AND INSTALLATION PROCEDURE	
3. PRODUCT USE	
4. PRODUCT MAINTENANCE	
5. TECHNICAL CHARACTERISTICS AND ASSEMBLY SCHEMES	5
FOR NOTES	
FOR NOTES	

1. GENERAL INFORMATION

Purpose and content of this document. This document contains a general description of the equipment, information on installation, intended use, maintenance, current repair and manufacturer's warranty.

Distribution of this document for product modifications. The manufacturer can make changes to the design of the product, aimed at improving its characteristics, changing the design, etc. This document may not contain a description of such changes, but applies to such modified products.

2. PRODUCT ASSEMBLY AND INSTALLATION PROCEDURE

Tools and accessories. The product does not include the tools required for assembly and installation. **Product assembly and installation procedure.**

- 1) Mark the area as indicated on the foundation layout scheme.
- 2) Dig the holes for the installation of the embedded parts and attachments. Levelling the depth of the holes by deepening them or adding gravel.
- 3) Assemble and install the equipment in accordance with the assembly schemes chapter 7.
- 4) Concrete the embedded parts and support structures of the attachments. When installing the product on sandy soil, the overall dimensions of the holes should be increased for 15-20%.

To avoid cracking of the wood, for screws with a diameter of more than 4 mm, drill holes with a diameter of 0.6...0.7 mm to a depth of 0.8 of the screw's length.

WARNING. The presence and participation of children during the installation of the product is not allowed.

3. PRODUCT USE

Do not use the product until it has been fully and completely installed.

The product must not be used by users of a different age and weight category.

Before using the product, clear the safety area of any unnecessary objects that may cause damage to the user (debris, tools left over from assembly and installation, etc.).

Do not use the product in adverse weather conditions (ice, snow, rain, hail, strong winds, etc.), which may cause injury to the user.

4. PRODUCT MAINTENANCE

You have purchased high-quality and reliable equipment. In the process of its production, the requirements of regulatory and technical documents of Ukraine, the CIS countries and the European Union regulating the production of children's gaming equipment were taken into account. However, it should not be forgotten that when operating any technical product, certain rules and requirements must be followed. Despite the fact that our product is of high quality and reliability, this rule applies to it in full. You should be aware that the implementation of the following rules and recommendations for product maintenance is aimed at ensuring that your child, the child of your friends or acquaintances is safe and no unforeseen factors threaten his health, life.

Remember that the operation of the product is accompanied by the influence of various negative factors on it, a complete list of which cannot be predicted. Among them, an important place is occupied by natural factors and factors caused by human influence on equipment. As a rule, their action initially leads to disruptions in the appearance of the product. Thus, under the influence of factors caused by the exploitation of a person, there may be damage to the integrity of the paint coating of parts made of wood, in the form of scuffs, chips, incisions, and when exposed to parts made of metal, damage to the paint coating in the form of nicks, chips, abrasion, etc. This leads to the emergence and development of defects that can be the cause of the destruction of the product. The product is particularly dangerous if it is used for other than its intended purpose, if the permissible loads are exceeded, or if vandalism occurs, as these factors can cause irreversible changes in the structure of the material from which the product is made, leading to destruction.

The maintenance of the product implies, first of all, the responsibility of the user to comply with all recommendations provided in this document, starting with a daily inspection of the external condition of the product before operation.

Daily inspection of the product is a very important procedure. With its help, you can timely detect any changes in the appearance of the product (deformation of individual parts, deformation of the structure as a whole or part of it, damage to parts, cracks of welds, as well as the absence of fastening of parts of the product, etc.).

Before using the product, check its operability, absence of damage, dirt on the product, sharp edges, reliability of fixing the structure, absence of unnecessary objects on the surface of the site. If the product is damaged, fully or partially inoperable, or has any other defects, do not use it.

During operation it is also necessary to inspect the condition of the product periodically - the current inspection. It includes an external inspection of the product, checking its operability (in the presence of moving elements - the smoothness of the movement of mechanisms, compliance with operating modes, etc.). Current inspection allows you to detect malfunctions caused by the operation of equipment, climatic conditions, acts of vandalism and other factors, until they reach a critical level and the destruction of the product. The current inspection is carried out in order to detect foreign objects that may threaten the user and lead to violations of the functioning of the product. The frequency of the current inspection is set by the owner taking into account the operating conditions. If you do not have sufficient technical knowledge and skills to conduct such inspections, we recommend you to contact the authorized specialists of the manufacturer in order to obtain advice.


Every three months, a scheduled inspection should be carried out, which primarily concerns the foundation part, load-bearing elements and connection nodes of elements (their integrity and degree of deterioration).

The main annual inspection must be carried out annually by authorised specialists of the manufacturer. During the inspection, the technical condition of the equipment shall be assessed for compliance with safety requirements. The degree of deterioration and damage to wooden elements and their ability to withstand the applied loads, damage, corrosion of metal elements and the impact of these factors on the safety of the product are determined. The inspection also helps to identify the impact of repairs, if any, on the safety of the equipment.


Based on the results of the inspection, a maintenance procedure is carried out to eliminate the identified discrepancies in the product's operation. This procedure includes assessing the condition of parts and assemblies, replacing worn parts, and restoring the integrity of protective coatings. The results of the inspections, as well as the procedures carried out as a result of the inspection and maintenance of the product must be properly documented in the Registration Journal, which is an integral part of this passport. The owner of the product must keep the acts of maintenance of the product, acts of repair work done.

5. TECHNICAL CHARACTERISTICS AND ASSEMBLY SCHEMES


	LK110
Length, mm	5828
Width, mm	3848
Height, mm	2899
Weight, kg	455
Fall height, mm	1230
Age range, years	from 3 to 7
Weight limits, kg	to 60




Picture 1 - Installation area and landing zone



Picture 2 – Layout scheme of foundations




Picture 3 – Tower assembly scheme 1.23-0.75 m




Pos.	Name	Weight, kg	Q-ty
1	Embedded element	2	7
2	Bolt M8*100		7
3	Bolt M6*30		16
4	Cup M8		7
5	Cap M8		7
6	Nut M8		7
7	Nut M6		16
8	Washer 10		7
9	Washer 8		16
10	Site (0.68x0.68)	6	2
11	Platform bracket		8
12	Cup M6		16
13	Cap M6		16
14	Screw 6.0x60 SPAX T-STAR plus (univers.)		16
15	Rack 1.6 m	6	1
16	Rack 2 m	8	1
17	Rack 1.8 m	7	1
18	Cap on bar		3
19	Screw 4x40		6
20	Screw 6x70		8
21	Rack 2.55 m	9	2
22	Rack 2.55 m	9	2
23	Front pediment	2	2
24	Back pediment	2	2
25	Bar 0.68 m	2	1

Picture 4 – Complete set of the tower 1.23-0.75 m




Pos.	Name	Weight, kg	Q-ty
1	Embedded element	2	8
2	Bolt M8*100		8
3	Bolt M6*30		24
4	Cup M8		8
5	Cap M8		8
6	Nut M8		8
7	Nut M6		24
8	Washer 10		8
9	Washer 8		24
10	Site (0.68x0.68)	6	3
11	Platform bracket		12
12	Cup M6		24
13	Cap M6		24
14	Screw 6.0x60 SPAX T-STAR plus (univers.)		24
15	Rack 2 m	8	1
16	Rack 1.6 m	6	1
17	Rack 1.8 m	7	2
18	Cap on bar		4
19	Screw 4x40		8
20	Screw 6x70		8
21	Rack 2.55 m	9	2
22	Rack 2.55 m	9	2
23	Front pediment	2	2
24	Back pediment	2	2
25	Bar 0.68 m	2	1

Picture 5 – Complete set of the triple tower (assembly scheme is identical to Picture 4)




Pos.	Name	Weight, kg	Q-ty	Pos.	Name	Weight, kg	Q-ty
1	Brace rod 493mm	1	1	13	Cap M8		4
2	Slide slip (angle)	5	1	14	Cup M8		4
3	Slide 1.2m	<i>34</i>	1	15	Stud M6x16 ISO7380		2
4	Slide support	2	1	16	Nut M8		4
5	Slide lining		2	17	Nut M6 DIN985		5
6	Upper sidepart right	4	1	18	Nut M8 DIN985		4
7	Upper sidepart left	4	1	19	Washer 6		3
8	Cover plate (120x510)		1	20	Washer 10		4
9	Stud M10x35 DIN7991	26	2	21	Washer 6x90		4
10	Stud M8x40 DIN7991	18	4	22	Screw with a drill	7	2
11	Stud M8x30 DIN7991	14	4]	6.3x32 DIN7504P	,	_
12	Stud M6x25 DIN7991	6	3	23	Screw 6.0x60 SPAX T-		4
					STAR plus with press		
					washer (univers.)		

Picture 6 – Slide assembly scheme 1.2m



Pos.	Name	Weight,	Q-ty
		kg	
1	Panel 0.6m "Window" right	4	1
2	Corner bracket 40x60		4
3	Screw 4x40		8
4	Cap M8		4
5	Cup M8		4
6	Nut M8		4
7	Washer 10		4
8	Stud M8x30 ISO7380		4

Picture 7 – Panel assembly scheme (assembling of other panels is identical)



For beams support and other elements

for the slides of the complex

A - shock-absorbing coating;

Б – soil;

B - concrete;

 Γ – depth of the shock-absorbing coating;

Д – product level plane;

E – game surface;

Й – thread.


Examples of impact-absorbing coatings

Material ¹	Description	Minimal depth,	Free fall		
		mm	height, mm		
Turf			≤ 1000		
Tree bark	grain size 20-80 mm	200	≤ 2000		
		300	≤ 3000		
Sawdust	grain size 5-30 mm	200	≤ 2000		
		300	≤ 3000		
Sand ²	grain size 0.2-2 mm	200	≤ 2000		
		300	≤ 3000		
Gravel ²	grain size 2-8 mm	200	≤ 2000		
		300	≤ 3000		
Another	HIC tested according to	According to	According to		
material	EN 1177	the test	the test		

^{1.} Materials are specially made for the playgrounds.


Picture 8 - Concreting scheme

^{2.} No clay inclusions should be present. Grain size is obtained by sieving through a sieve as in EN 933-1.




Picture 9

Pos.	Name	Weight, kg	Q-ty	Pos.	Name	Weight, kg	Q-ty
1	Corner bracket 40x60		42	36	Panel "Fruits" assembly	6	1
2	Brace rod (L=600mm)	1	7	37	Crossbar of the rape net	10	1
3	Brace rod 493 mm	1	1	38	Arc rope net	11	1
4	Slide slip (angle)	5	1	39	Rope embedding (angle)	4	2
5	Panel "Puzzle" assembly	5	1	40	Rope embedding (angle)	4	1
6	Panel "Cat in the window"	5	1	41	Tube d12x1.5, L=22 mm		12
7	Panel for drawing	8	1	42	Cap M8		72
8	Handle		2	43	Cup M8		<i>72</i>
9	Coverings	2	4	44	Cup M6		4
10	Table with numbers		1	45	Cap M8		4
11	Angle bar of the show window		2	46	Bolt M6*30		4
12	Angle bar of the table		2	47	Bolt M8*45		14
13	Tower (Mini) 1.23-0.73 m	95	1	48	Stud M6x16 ISO7380		2
14	Triple tower	111	1	49	Stud M6x25 DIN7991		11
15	Platform bracket		1	50	Stud M6x30 DIN7991		8
16	Connector	2	1	51	Stud M8x30 DIN7991		4
17	Slide 1.2 m	34	1	52	Stud M8x30 ISO7380		46
18	Slide support	2	1	53	Stud M8x40 DIN7991		2
19	Slide lining		2	54	Stud M10x35 DIN7991		2
20	Upper sidepart right	4	1	55	Nut M6		4
21	Upper sidepart left	4	1	56	Nut M8		58
22	Cover plate (120x510)		1	57	Nut M6 DIN985		5
23	Climber's shield	24	1	58	Nut M8 DIN985		4
24	Panel "Cat birds"	5	1	59	Cap nut M6 DIN1587		16
25	Panel 0.6m "Window" right	5	2	60	Cap nut M8 DIN1587		4
26	Panel 0.6m "Window" left	5	2	61	Washer 6		4
27	Panel "World's map"	6	1	62	Washer 6		4
28	Game console "What does anyone eat"	12	1	63	Washer 6		3
29	Panel "Show window"	4	1	64	Washer 8		4
30	Balcony	14	1	65	Washer 10		<i>72</i>
31	Balcony floor 0.72m	3	1	66	Screw 4x40		84
32	Game panel "School"	8	1	67	Screw 6x90		4
33	Balcony pallet	5	1	68	Screw with a drill 6.3x32 DIN7504P		2
34	Arc balcony	13	1	69	Screw 6.0x60 SPAX T-STAR plus (univers.)		128
35	Panel "Disc"	9	1				_



Picture 11



Picture 12