

interatletika™

PRODUCTION AND SALE OF SPORTS GOODS

Customer support:


+38 095 273 81 53

play.interatletika.com

DATA SHEET

Swing TE402, TE404, TE402M,
TE404M

The product meets the requirements of EN 1176-1:2009 and EN 1176-2:2008



CONTENT

1. GENERAL INFORMATION.....	4
2. MAIN TECHNICAL DATA AND CHARACTERISTICS.....	4
3. COMPLETENESS AND CHARACTERISTICS OF THE MAIN PARTS OF THE PRODUCT.....	6
4. PROCEDURE FOR ASSEMBLING AND INSTALLING THE PRODUCT.....	7
5. PRODUCT INSTALLATION SCHEME.....	8
6. INFORMATION ON STORAGE, TRANSPORTATION AND DISPOSAL.....	9
7. PRODUCT USE.....	10
8. PRODUCT MAINTENANCE.....	10

FOR NOTES

[illegible]

1. GENERAL INFORMATION


Purpose and content of this document. This document contains a general description of the equipment, information on installation, intended use, maintenance, current repair and manufacturer's warranty.

Distribution of this document for product modifications. The manufacturer can make changes to the design of the product, aimed at improving its characteristics, changing the design, etc. This document may not contain a description of such changes, but applies to such modified products.


2. MAIN TECHNICAL DATA AND CHARACTERISTICS

	TE402	TE404	TE402M	TE404M
Length, mm	2255	3655	2255	3660
Width, mm	1362	1362	1362	1362
Height, mm	2086	2086	2086	2086
Weight, kg	84	95	90	104
Fall height, mm	1190	1190	1230	1230
Age restrictions, years	from 3 to 12	from 3 to 12	from 3 to 12	from 3 to 12
Weight limits, kg	up to 60	up to 60	up to 60	up to 60


TE402 – Single swing on wooden uprights



TE404 - Double swing on the wooden uprights




TE402M – Single swing on chains



- 1 - Single swing on wooden uprights.
2 - Seat with backrest on chains.

TE404M - Double swing on chains



- 1 - Double swing on wooden uprights.
2 - Seat with backrest on chains.

Pic. 1

3. COMPLETENESS AND CHARACTERISTICS OF THE MAIN PARTS OF THE PRODUCT

Table 1 – For TE402, TE404.

Nº	Name	Quantity	Weight, kg
1	Beam with swing	1	25(35**)
2	Support	4	2
3	Bar	4	7
4	Cap	4	
5	Cap	4	
6	Cap M10, M12	8	
7	Cup M10, M12	8	
8	Cap M8	4	
9	Cup M8	4	
10	Bolt M8x120 GOST7802	4	
11	Bolt M10x120 GOST7802	8	
12	Nut M8 GOST 5915	4	
13	Nut M10 GOST 5915	8	
14	Washer 10 GOST11371*	8	
15	Washer 10 GOST6958*	8	
16	Washer 12 GOST11371	8	
17	Washer 12 GOST6402*	8	
18	Screw 8x50 GOST11473	4	

* GOST 11371 – Flat washers (of normal accuracy). Technical conditions

GOST 6402 – Spring washers. Technical conditions

**** for swing TE404

Table 2 – For TE402M

Pos.	Name	Weight, kg	Q-ty
1	Support	2	4
2	Brace rod	20	1
3	Bearing housing assembly	3	2
4	Bar 2058 mm	12	4
5	Cap		4
6	Cap		4
7	Cap M10, M12		12
8	Cup M10, M12		8
9	Cap M8		4
10	Cup M8		4
11	Cap M8		4
12	Bolt M8x120 GOST7802		4
13	Bolt M10x120 GOST7802		8
14	Nut M8 GOST5915		4
15	Nut M10 GOST5915		8
16	Washer 10 GOST11371		8
17	Washer 10 GOST6958		8
18	Washer 12 GOST11371		8
19	Washer 12 GOST6402		8
20	Screw 8x50 GOST11473		4

Table 3 – For TE404M


Pos.	Name	Weight, kg	Q-ty
1	Support	2	4
2	Bearing housing assembly	3	4
3	Swing beam (2seats)	26	1
4	Bar 2180 mm	12	4
5	Cap		4
6	Cap		4
7	Cap M10, M12		16
8	Cup M10, M12		8
9	Cap M8		4
10	Cup M8		4
11	Cap M8		8
12	Bolt M8x120 GOST7802		4
13	Bolt M10x120 GOST7802		8
14	Nut M8 GOST5915		4
15	Nut M10 GOST5915		8
16	Washer 10 GOST11371		8
17	Washer 10 GOST6958		8
18	Washer 12 GOST11371		8
19	Washer 12 GOST6402		8
20	Screw 8x50 GOST11473		4

4. PROCEDURE FOR ASSEMBLING AND INSTALLING THE PRODUCT

Tools and accessories. The product does not include the tools required for installation.


The procedure for assembling and installing the product.

1) Assemble the product according to pic. 2.



Pic. 2

2) Install the product according to pic. 3. During installation on sandy soil, the overall dimensions of the foundation should be increased by a 15-20%.



Pic. 3

A - shock-absorbing coating;

B – soil;

C – concrete;

D- depth of the shock absorbing coating;

E - product level plane;

F – game surface.


Examples of impact-absorbing coatings


Material ¹	Description	Minimal depth, mm	Fall height, mm
Turf			≤ 1000
Tree bark	grain size 20-80 mm	200	≤ 2000
		300	≤ 3000
Sawdust	grain size 5-30 mm	200	≤ 2000
		300	≤ 3000
Sand ²	grain size 0.2-2 mm	200	≤ 2000
		300	≤ 3000
Gravel ²	grain size 2-8 mm	200	≤ 2000
		300	≤ 3000
Another material	HIC tested according to EN 1177	According to the test	According to the test
1. Materials are specially made for the playgrounds. 2. No clay inclusions should be present. Grain size is obtained by sieving through a sieve as in EN 933-1.			

5. PRODUCT INSTALLATION SCHEME

Safety zone of the installed product must comply with pic. 4

Safety zone for TE402, TE402M





Pic. 4

6. INFORMATION ON STORAGE, TRANSPORTATION AND DISPOSAL

The product is transported in the manufacturer's packaging by any means of transport that ensures its safety and protection from external factors (rain, snow, sunlight, water, high humidity, etc.).

Information about transportation

Date		Brand, state number of the ca/trailer	Position, full name	Signature
Departure	Arrival			

Before installation, store the product in the original packaging in dry, closed rooms with natural air ventilation.

If it is necessary to transport the product to another location after use, it is recommended to use the manufacturer's packaging.

If long-term storage of the product is required, the following storage rules must be observed (the list of conditions is not complete):

- place the product in a closed dry room with natural ventilation;
- protect the product from external factors (dust, water drops, etc.) with a large plastic bag, leaving space for free air circulation;

- take other measures to preserve the appearance and characteristics of the product during storage.

When removing the product from storage and preparing for installation, follow the next recommendations:

- remove the product from the packaging material (polyethylene, cardboard, other packaging materials);
- remove dust and other contaminants from the surface of the product;
- check completeness and absence of parts damage.

Storage information

Date		Product storage conditions	Full name	Signature
Putting into storage	Removal from storage			

After the end of the equipment's service life, the buyer independently determines the procedure for its use. If you decide to recycle, contact the seller or specialized organizations.

The equipment does not contain harmful impurities and materials that can harm your health and is not subject to special recycling.

7. PRODUCT USE

Do not use the product until it has been fully and completely installed.

The product must not be used by users of a different age category.

The product must not be used by users of a different weight category.

Before using the product, clear the safety area of any unnecessary objects that may cause damage to the user (debris, tools left over from assembly and installation, etc.).

Do not use the product in adverse weather conditions (ice, snow, rain, hail, strong winds, etc.), which may cause injury to the user.

8. PRODUCT MAINTENANCE

You have purchased high-quality and reliable equipment. In the process of its production, the requirements of regulatory and technical documents of Ukraine, the CIS countries and the European Union regulating the production of children's gaming equipment were taken into account. However, it should not be forgotten that when operating any technical product, certain rules and requirements must be followed. Despite the fact that our product is of high quality and reliability, this rule applies to it in full. You should be aware that the implementation of the following rules and recommendations for product maintenance is aimed at ensuring that your child, the child of your friends or acquaintances is safe and no unforeseen factors threaten his health, life.

Remember that the operation of the product is accompanied by the influence of various negative factors on it, a complete list of which cannot be predicted. Among them, an important place is occupied by natural factors and factors caused by human influence on equipment. As a rule, their action initially leads to disruptions in the appearance of the product. Thus, under the influence of factors caused by the exploitation of a person, there may be damage to the integrity of the paint coating of parts made of wood, in the form of scuffs, chips, incisions, and when exposed to parts made of metal, damage to the paint coating in the form of nicks, chips, abrasion, etc. This leads to the emergence and development of defects that can be the cause of the destruction of the product. The product is particularly dangerous if it is used for other than its intended purpose, if the permissible loads are exceeded, or if vandalism occurs, as these factors can cause irreversible changes in the structure of the material from which the product is made, leading to destruction.

The maintenance of the product implies, first of all, the responsibility of the user to comply with all recommendations provided in this document, starting with a daily inspection of the external condition of the product before operation.

Daily inspection of the product is a very important procedure. With its help, you can timely detect any changes in the appearance of the product (deformation of individual parts, deformation of the structure as a whole or part of it, damage to parts, cracks of welds, as well as the absence of fastening of parts of the product, etc.).

Before using the product, check its operability, absence of damage, dirt on the product, sharp edges, reliability of fixing the structure, absence of unnecessary objects on the surface of the site. If the product is damaged, fully or partially inoperable, or has any other defects, do not use it.

During operation it is also necessary to inspect the condition of the product periodically - the current inspection. It includes an external inspection of the product, checking its operability (in the presence of moving elements - the smoothness of the movement of mechanisms, compliance with operating modes, etc.). Current inspection allows you to detect malfunctions caused by the operation of equipment, climatic conditions, acts of vandalism and other factors, until they reach a critical level and the destruction of the product. The current inspection is carried out in order to detect foreign objects that may threaten the user and lead to violations of the functioning of the product. The frequency of the current inspection is set by the owner taking into account the operating conditions. If you do not have sufficient technical knowledge and skills to conduct such inspections, we recommend you to contact the authorized specialists of the manufacturer in order to obtain advice.

Every three months, a scheduled inspection should be carried out, which primarily concerns the foundation part, load-bearing elements and connection nodes of elements (their integrity and degree of deterioration).

The main annual inspection must be carried out annually by authorised specialists of the manufacturer. During the inspection, the technical condition of the equipment shall be assessed for compliance with safety requirements. The degree of deterioration and damage to wooden elements and their ability to withstand the applied loads, damage, corrosion of metal elements and the impact of these factors on the safety of the product are determined. The inspection also helps to identify the impact of repairs, if any, on the safety of the equipment.

Based on the results of the inspection, a maintenance procedure is carried out to eliminate the identified discrepancies in the product's operation. This procedure includes assessing the condition of parts and assemblies, replacing worn parts, and restoring the integrity of protective coatings. The results of the inspections, as well as the procedures carried out as a result of the inspection and maintenance of the product must be properly documented in the Registration Journal, which is an integral part of this passport. The owner of the product must keep the acts of maintenance of the product, acts of repair work.

